



Eclipse MTE28VGM Plastic Casing Replacement

This guide will show you how to replace the plastic casing for the Eclipse MTE28VGM.

Written By: Grant G



INTRODUCTION

Replacing the case is relatively simplistic and requires only the use of a screwdriver, plastic remover tools, and takes about 1 hour to complete.



TOOLS:

- [JIS Driver Set](#) (1)
-

Step 1 — Plastic Casing Replacement



- Using the screwdriver with the J00 bit, remove the two 4.8 mm Phillips screws.

⚠ Use caution when removing the screws as they can strip easily.

Step 2



- Using the small metal pry bar, remove the bottom plastic cover.
- Using your thumb, press down on the home button and hold the metal casing. With your other hand hold the top plastic part of the device. At the same time slide the metal casing and the plastic casing apart.
- ⓘ On occasion the battery can become swollen and make this process difficult. You might need to use the spudger to push on the bottom components to assist in the separation.

Step 3



- Using the screwdriver, remove the four 4.8 mm Phillips head J00 screws at each corner of the motherboard.
- Remove the motherboard from the front plastic cover and screen.
- Install new plastic case following steps in reverse order

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-07-13 06:17:36 AM.